





## NEUTRAL BAR OVERVIEW MAIN LINE NEUTRAL BARS

B22

### General Information


Unassembled for the use of manufacturers of Switch and Panel Boards who may find it convenient to produce special neutral bar assemblies, suitable for their own particular needs. A fast and secure connection is assured by inserting the wire into the "V" shaped hole and tightening the screw. The bars are constructed of pure electrolytic seamless copper tubing, ensuring high conductivity and superior strength.

### AVAILABLE SCREW TYPES

SCREW TYPE 1		SCREW TYPE 2	
	<b>STYLE:</b> HEADLESS SET SCREW. <b>SLOT:</b> SLOTTED <b>MATERIAL:</b> STEEL ZINC PLATED		<b>STYLE:</b> HEADED MACHINE SCREW. <b>SLOT:</b> SLOTTED <b>MATERIAL:</b> STEEL ZINC PLATED
SCREW TYPE 3		SCREW TYPE 4	
	<b>STYLE:</b> HEADED MACHINE SCREW. <b>SLOT:</b> COMBINATION SQUARE, SOCKET/SLOT <b>MATERIAL:</b> STEEL ZINC PLATED		<b>STYLE:</b> HEADLESS SET SCREW. <b>SLOT:</b> HEX SOCKET/SLOT <b>MATERIAL:</b> ALUMINUM TIN PLATED

\* NORMALLY SUPPLIED WITH TYPE 1

### TYPE N70 - 70 AMP MAIN LINE NEUTRAL BAR ASSEMBLIES - 14-4 AWG



ITEM NUMBER	NO. OF CIRCUIT TAPS	RANGE LOAD	LENGTH	HEIGHT WITH MAX COND	WIDTH	TWO MOUNTING HOLES
N70-4	4	14-6	2.750	.750	.344	.203*
N70-6	6	14-6	3.500	.750	.344	.203*
N70-8	8	14-6	4.438	.750	.344	.203*
N70-10	10	14-6	5.125	.750	.344	.203*
N70-12	12	14-6	5.938	.750	.344	.203*
N70-14	14	14-6	6.687	.750	.344	.203*

### TYPE N125 - 125 AMP MAIN LINE NEUTRAL BAR ASSEMBLIES - 1/0-2 AWG

ITEM NUMBER	NO. OF CIRCUIT TAPS	RANGE LOAD	LENGTH	HEIGHT WITH MAX COND	WIDTH	TWO MOUNTING HOLES
N125-16	16	14-6	4.750	1.438	1.344	.203*
N125-20	20	14-6	5.500	1.438	1.344	.203*
N125-22	22	14-6	5.750	1.438	1.344	.203*
N125-24	24	14-6	6.312	1.438	1.344	.203*
N125-26	26	14-6	6.500	1.438	1.344	.203*
N125-28	28	14-6	7.125	1.438	1.344	.203*
N125-30	30	14-6	7.132	1.438	1.344	.203*

\*PLEASE SPECIFY MOUNTING HOLE POSITION